

Securi Mesh Gates

Welded Mesh Panels | Jacksons Security

Jacksons Fencing

Stowting Common | Ashford | TN25 6BN

www.jacksons-security.co.uk

+44 (0) 1233 750 393

Jacksons

Quality that lasts

Fencing & Access Solutions



Double Leaf Swing Gate



180° Adjustable Hinge



Standard Lock

Securi-Mesh Gates

Available as single and double swing gates with manual operation or automated with underground, ram or safety-glide in-stile operators.

Securi-Mesh Cantilever Sliding Gates

Securi-Mesh Sliding Gates are ideal for applications where space may be restricted, the ground unlevel, or where a substantial single gate would provide higher levels of security.

The gates are smooth and virtually silent in operation, supported on a special carriage so that a single leaf is able to span widths of up to 8m over track, road, rail or even water.

Gate panels are constructed to the same exacting standards as Securi-Mesh fencing and are mounted on a substantial bottom rail of formed steel with square section steel support posts with crash rated versions available (see High Security Perimeter and Access Control brochure).



Securi Mesh Gates

Securi-Mesh Single and Double Swing Gates

- Welded frame design
- Available in a range of standard widths up to 10m and heights to 3m for pedestrian and vehicular access
- Optional mounting brackets for high security locking devices
- **Single gates** are supplied as right hand hanging, opening inwards (unless specified) and are complete with key lock, handles and gate stop
- **Double gates** are supplied complete with key lock, handles, centre gate stop and drop bolts
- 180° opening, adjustable, tamper-proof hinges
- Additional welded support rails subject to leaf width
- 60mm x 60mm section framing rails
- Square section posts at 100mm, 120mm, 150mm and 250mm subject to size of gate
- Gate posts supplied to allow 800mm - 1.0m in ground or with base plates for bolting onto concrete
- Can be extended in height to carry barbed/razor wire, Rota-Spike or other high security extras
- Suitable for automated operation

Finishes

- Galvanized to BS EN 1461 as standard
- Galvanized and powder coated to BS EN 13438 in one of our standard colours at extra cost
- Powder coated to any other BS and RAL colour to special order

Cantilever Sliding Gates

- Ideal for applications where space is limited or ground obstacles need to be spanned
- Effective operation in applications subject to high wind loading
- Available in a range of standard widths to span up to 16m and in heights to 3m
- Gates to span greater widths available to special order
- Substantial construction ensures safe, reliable operation
- Supplied complete with key in lock and handles
- Heavy duty carriage for smooth, quiet operation
- 2 rail plus substantial formed steel bottom rail design
- 60mm x 40mm rails
- 120mm x 80mm portals
- Portals supplied with base plates for bolting onto concrete
- Posts can be extended to accommodate gate top mounted physical security devices
- Automated operation ready

Tracked Sliding Gates

We are able to supply any Securi-Mesh gates for tracked sliding operating on level ground if required for exceptionally heavy designs or where a single gate leaf exceeds 8m.

